

REV.	DESCRIPTION	DRAW.	DATE.
01	新发行图纸	Elih	2016.05.05

No. of Pins	Dimension	
	DIM.B	DIM.A
03	7.50	12.00
04	10.00	14.50
05	12.50	17.00
06	15.00	19.50
07	17.50	22.00
08	20.00	24.50
09	22.50	27.00
10	25.00	29.50
11	27.50	32.00

NOTE:

1. MATERIAL:
 - 1.1 HOUSING: PA9T, UL 94V-0
 - 1.2 TERMINAL: C2680
2. FINISH:
 - 2.1 TERMINAL: NICKEL 50 u"MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA OR Tin ON THE SOLDERING AREA.
3. PRODUCT SPECIFICATION
 - 3.1 CURRENT RATING :5A
 - 3.2 VOLTAGE RATING : 30V AC
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - 3.4 INSULATION RESISTANCE: 100MΩ min.
 - 3.5 CONTACT RESISTANCE: 30mΩ Max.
 - 3.6 Operating Temperature: -40° ~105°

DISONG ELECTRONIC CO.,LTD.

UNLESS OTHERWISE SPECIFIED,TOLERANCE: X. ±0.25 X.x ±0.10 X.xx ±0.05 ANGULAR ±2°	DESIGN		DATE		TITLE:	
	APPROVED		DATE		B06M-B-R4左防呆	
	PART NO			REV: 01	SCALE: 1:1	UNIT: mm
	DRAWING NO			SIZE: A4	SHEET: 1/1	

Recommended P.C.B Layout

Layout Tolerance=+/-0.05mm

