

REV.	DESCRIPTION	DRAW.	DATE.
01	新发行图纸	Elih	2016.05.05

No. of Pins	Dimension	
	DIM.B	DIM.A
03	7.50	12.00
04	10.00	14.50
05	12.50	17.00
06	15.00	19.50
07	17.50	22.00
08	20.00	24.50
09	22.50	27.00
10	25.00	29.50

Material

Insulator : Nylon 9T (UL94V-0)

Contact : C2680

Contact Plated : Gold over Nickel or Tin

Specification

Current Rating :7A

Instant Current :10A

Contact Resistance : 30mΩ

Insulation Resistance : 100MΩ

Dielectric Voltage : 500V

Operating Temperature : -40°~105°

DISONG ELECTRONIC CO., LTD.

UNLESS OTHERWISE SPECIFIED,TOLERANCE: X. ±0.25 X.x ±0.10 X.xx ±0.05 ANGULAR ±2°	DESIGN		DATE		TITLE: BATTERY 2.5PITCH MALE CONNECTOR
	APPROVED		DATE		
	PART NO	B06M-B-R4 右糖果	REV: 01	SCALE: 1:1	UNIT: mm
	DRAWING NO	B06M-B-R4 右糖果	SIZE: A4	SHEET: 1/1	

Recommended P.C.B Layout

Layout Tolerance=+/-0.05mm