



REV.	DESCRIPTION	DRAW.	DATE.

No. of Pins	Dimension				
	DIM.A	DIM.B	DIM.C	DIM.D	DIM.E
03	7.50	11.50	14.45	10.50	2.0/3.0
04	10.00	14.00	16.95	13.00	2.0/3.0
05	12.50	16.50	19.45	15.50	2.0/3.0
06	15.00	19.00	21.95	18.00	2.0/3.0
07	17.50	21.50	24.45	20.50	2.0/3.0
08	20.00	24.00	26.95	23.00	2.0/3.0
09	22.50	26.50	29.45	25.50	2.0/3.0
10	25.00	29.00	31.95	28.00	2.0/3.0

Material
 Insulator : Nylon 6T (UL94V-0)
 Contact : Phosphor Bronze
 Contact Plated : Gold over Nickel or Tin

Specification
 Current Rating : 5A
 Instant Current : 7A
 Contact Resistance : 30mΩ
 Insulation Resistance : 100MΩ
 Dielectric Voltage : 500V
 Operating Temperature : -40°~105°

DISONG ELECTRONIC CO.,LTD.

UNLESS OTHERWISE SPECIFIED, TOLERANCE: X. ±0.20 X.x ±0.10 X.xx ±0.05 ANGULAR ±2°	DESIGN	Y.Q.H	DATE	2014.08.26	TITLE:	
	APPROVED		DATE		B02F-B-S2	
	PART NO		REV: 01		SCALE: 1:1	UNIT: MM
	DRAWING NO		SIZE: A4		SHEET: 1/1	