

REV.	MODIFICATION	ECN No.	NAME	DATE
AO	△新版发行		宋亮红	2017-02-24

NOTES:

1.MATERIAL:

MOLDING: LCP UL94 V-0
CONTACT: COPPER ALLOY.
GOLD PLATED Min ON CONTACT AREA, 100u"
Min TIN (LEAD FREE) ON SOLDER AREA,
SHELL: SUS304-H, T=0.30±0.03mm
50u" NICKEL PLATING OVER ALL.

2.MECHANICAL:

INSERTION: 5~20N.
EXTRACTION: 8~20N AFTER TEST.
DURABILITY: 10000 CYCLES

3.ELECTRICAL:

CURRENT: 3A FOR VBUS;
1.25A FOR GND PIN.
025A FOR OTHER.

VOLTAGE: 20 V MAX
WITHSTANDING VOLTAGE: 100V AC R.M.S.
CONTACT RESISTANCE: 40mΩ MAX.
INSULATION RESISTANCE: 100MΩ MIN.

4.ENVIRONMENTAL

TEMPERATURE RANGE -25°C ~ +85°C

5. 尺寸标注事项:

图示有标示⊗者为首样全检, 重点管控尺寸.

6. 材料RoHS







Table:

成品料号	零件名称	零件料号	材料 / 电镀	
TX	端子	TX	SUS 304 R-H	NO PLATING
	焊脚	TX	SUS 301 R-H	Sn 80~200u"
	外壳	TX	SUS 301 R-H	电镀切料带后.

迪松电子 (DISONG)

.X: ±0.35	.X': ±1.5"	INTENDED USE: CONNECTOR	TITLE: TYPE-C 2P 直插母座	
.XX: ±0.25	.XX': ±1.0"		DRG. NO.:	
.XXX: ±0.20	.XXX': ±0.5"	APPD.:	PART NO.:	
MAT'L.:		CHKD.:	SCALE: 1:1	PAGE: 1/1
SEE NOTES	⊗	DR.:	Len.Song	REV.:
FINISH:			UNIT: mm	AO