

REV.	MODIFICATION	ECN No.	NAME	DATE
AO	新版发行		宋亮红	2017-02-24

NOTES:

1.MATERIAL:

MOLDING: LCP UL94 V-0
CONTACT: COPPER ALLOY.
GOLD PLATED Min ON CONTACT AREA, 100u"
Min TIN (LEAD FREE) ON SOLDER AREA,
SHELL: SUS304-H,T=0.30±0.03mm
50u" NICKEL PLATING OVER ALL.

2.MECHANICAL:

INSERTION: 5~20N.
EXTRACTION: 8~20N AFTER TEST.
DURABILITY: 10000 CYCLES

3.ELECTRICAL:

CURRENT: 3A FOR VBUS;
1.25A FOR GND PIN.
0.25A FOR OTHER.
VOLTAGE: 20 V MAX
WITHSTANDING VOLTAGE: 100V AC R.M.S.
CONTACT RESISTANCE: 40mΩ MAX.
INSULATION RESISTANCE: 100MΩ MIN.

4.ENVIRONMENTAL

TEMPERATURE RANGE -25°C ~ +85°C

5. 尺寸标注事项:

图示有标示者为首样全检, 重点管控尺寸.

6. 产品符合RoHS标准.






Table:

成品料号	零件名称	零件料号	材料 / 电镀
TX	端子 molding半成品	TX	SUS304 RH NO PLATING
	塑胶材料	TX	SUS301 RH Sn 80~200u"
	外壳	TX	SUS301 RH 电镀切料带后.

迪松电子 (DISONG)

.X: ±0.35	.X*: ±1.5"	INTENDED USE: CONNECTOR		TITLE: TYPE-C 2P 焊线式	
.XX: ±0.25	.XX*: ±1.0"				
.XXX: ±0.20	.XXX*: ±0.5"	APPD.:		PART NO.:	
MAT'L:		CHKD.:		DWG. NO.:	USB-310A
SEE NOTES				SCALE: 1:1	PAGE: 1/1
FINISH:		DR.: Len.Song		UNIT: mm	REV.: AO