






RoHS  
Compliant

SYMBOL	REVISION	APPROVAL	DATE



NOTE:  
Material  
Insulator: LCP  
Contact: C2680  
Contact Plated: Gold over Nickel or Tin  
Specification  
Current rating: 3A  
instant CURRENT: 5A  
Contact Resistance: 30mΩ  
Insulation Resistance: 100MΩ  
Dielectric Voltage: 500V  
Operating Temperature: -40~105°



RECOMMENDED P.C.B LAYOUT  
TOP VIEW (.XX±0.05)

2	HOUSING	LCP	1	GRAY
1	CONTACT TERMINAL	C2680	2	Au PLATED
	NO.	MATERIAL	QTY.	FINISHING

DISONG ELECTRONIC CO., LTD.

PART NAME	CONNECTOR		DRAWING	Y.C.Zhang	DWG.No.	
PART NO.	A00M-2P-R5		CHECK	G.C.Chen	REV.	A1
UNIT:	TOLERANCE	UP TO 5	APPROVAL		DATE	01-05-2020
mm	OTHERWISE	ABOVE 30	SCALE	2:1	PAGE	1 OF 1
		∅0.2				
		∅0.3				
		∅0.5				
		∅1.3				
		ANGLE				
		0°±3'				

COPYRIGHT RESERVED, PLEASE DO NOT COPY.