



REV.	DESCRIPTION	DRAW.	DATE.

- NOTE:
- MATERIAL:
    - HOUSING: PA9T, UL 94V-0
    - TERMINAL: Phosphor Bronze
  - FINISH:
    - TERMINAL: NICKEL 50  $\mu$ M IN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Tin ON THE SOLDERING AREA.
  - PRODUCT SPECIFICATION
    - CURRENT RATING :5A
    - VOLTAGE RATING : 30V AC
    - DIELECTRIC WITHSTANDING VOLTAGE:500VAC
    - INSULATION RESISTANCE: 100M $\Omega$  min.
    - CONTACT RESISTANCE: 30m $\Omega$  Max.
    - Operating Temperature: -40° ~105°

RECOMMENDED PCB LAYOUT  
 T=1.2MM,TOLERANCES $\pm$ 0.05MM

**DISONG ELECTRONIC CO., LTD**

UNLESS OTHERWISE SPECIFIED, TOLERANCE:	DESIGN	W.LH	DATE	2017.03.28	TITLE:
X. iA0.5	APPROVED		DATE		DS-B01F-A-15P-S2
X.x iA0.35	PART NO			REV: 01	SCALE: 1:1
X.xx iA0.25	DRAWING NO			SIZE: A4	UNIT: MM
ANGULAR iA2i $\bar{6}$				SHEET: 1/1	