



REV.	DESCRIPTION	DRAW.	DATE.

- NOTE:
- MATERIAL:
 - HOUSING: PA9T, UL 94V-0
 - TERMINAL: C2680
 - FINISH:
 - TERMINAL: NICKEL 50 μ M MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Sn ON THE SOLDERING AREA.
 - PRODUCT SPECIFICATION
 - CURRENT RATING :5A
 - VOLTAGE RATING : 30V AC
 - DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - INSULATION RESISTANCE: 100M Ω min.
 - CONTACT RESISTANCE: 30m Ω Max.
 - Operating Temperature: -40' ~105'

RECOMMENDED PCB LAYOUT
 T=1.2MM,TOLERANCES \pm 0.05MM

DISONG ELECTRONIC CO., LTD

UNLESS OTHERWISE SPECIFIED, TOLERANCE:	DESIGN	W. I. H	DATE	2017.09.28	TITLE:
X.	APPROVED		DATE		DS-B01M-A-16P-R2
X.x	PART NO		REV: 01	SCALE: 1:1	UNIT: MM
X.xx	DRAWING NO		SIZE: A4	SHEET: 1/1	
ANGULAR					