



REV.	DESCRIPTION	DRAW.	DATE.

- NOTE:
- MATERIAL:
 - HOUSING: PA9T, UL 94V-0
 - TERMINAL: Phosphor Bronze
 - FINISH:
 - TERMINAL: NICKEL 50 μ"MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Tin ON THE SOLDERING AREA.
 - PRODUCT SPECIFICATION
 - CURRENT RATING :5A
 - VOLTAGE RATING : 30V AC
 - DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - INSULATION RESISTANCE: 100MΩ min.
 - CONTACT RESISTANCE: 30mΩ Max.
 - Operating Temperature: -40° ~105°

RECOMMENDED PCB LAYOUT
T=1.2MM, TOLERANCES±0.05MM

DISONG ELECTRONIC CO., LTD				
UNLESS OTHERWISE SPECIFIED, TOLERANCE:	DESIGN	W.LH	DATE	TITLE:
X. iA0.5	APPROVED		2017.03.28	DS-B01F-A-13P-S2
X.x iA0.35			DATE	
X.xx iA0.25	PART NO		REV: 01	SCALE: 1:1
ANGULAR iA2i0	DRAWING NO		SIZE: A4	UNIT: MM
			SHEET: 1/1	