



REV.	DESCRIPTION	DRAW.	DATE.

NOTE:

1. MATERIAL:
 - 1.1 HOUSING: PA9T, UL 94V-0
 - 1.2 TERMINAL: Phosphor Bronze
2. FINISH:
 - 2.1 TERMINAL: NICKEL 50 μ"MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Tin ON THE SOLDERING AREA.
3. PRODUCT SPECIFICATION
 - 3.1 CURRENT RATING :5A
 - 3.2 VOLTAGE RATING : 30V AC
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - 3.4 INSULATION RESISTANCE: 100MΩ min.
 - 3.5 CONTACT RESISTANCE: 30mΩ Max.
 - 3.6 Operating Temperature: -40° ~105°

RECOMMENDED PCB LAYOUT
 T=1.2MM,TOLERANCES±0.05MM

DISONG ELECTRONIC CO., LTD			
DESIGN	W.LH	DATE	2017.03.28
APPROVED		DATE	
PART NO		REV: 01	SCALE: 1:1
DRAWING NO		SIZE: A4	SHEET: 1/1
		TITLE:	DS-B01F-A-16P-S2
		UNIT: MM	

UNLESS OTHERWISE SPECIFIED, TOLERANCE:	
X.	±0.5
X.x	±0.35
X.xx	±0.25
ANGULAR	±0.25