



REV.	DESCRIPTION	DRAW.	DATE.

NOTE:

1. MATERIAL:
  - 1.1 HOUSING: PA9T, UL 94V-0
  - 1.2 TERMINAL: C2680
2. FINISH:
  - 2.1 TERMINAL: NICKEL 50 μ<sup>m</sup> MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Sn ON THE SOLDERING AREA.
3. PRODUCT SPECIFICATION
  - 3.1 CURRENT RATING :5A
  - 3.2 VOLTAGE RATING : 30V AC
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC
  - 3.4 INSULATION RESISTANCE: 100MΩ min.
  - 3.5 CONTACT RESISTANCE: 30mΩ Max.
  - 3.6 Operating Temperature: -40° ~105°

DISONG ELECTRONIC CO., LTD.

UNLESS OTHERWISE SPECIFIED, TOLERANCE:	DESIGN	DATE	2020.10.18	TITLE:
X	APPROVED	DATE		1.5间距公座-10P-90度-T0.4
X.x	PART NO	REV: 01		SCALE: 1:1
X.xx	DRAWING NO	SIZE: A4		UNIT: MM
ANGULAR	DS-A-10P-R4	SHEET: 1/1		