



REV.	DESCRIPTION	DRAW.	DATE.

- NOTE:
- MATERIAL:
 - HOUSING: PA9T, UL 94V-0
 - TERMINAL: C2680
 - FINISH:
 - TERMINAL: NICKEL 50 μ^mMIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Sn ON THE SOLDERING AREA.
 - PRODUCT SPECIFICATION
 - CURRENT RATING :5A
 - VOLTAGE RATING : 30V AC
 - DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - INSULATION RESISTANCE: 100MΩ min.
 - CONTACT RESISTANCE: 30mΩ Max.
 - Operating Temperature: -40° ~105°

RECOMMENDED PCB LAYOUT
 T=1.2MM,TOLERANCES±0.05MM

DISONG ELECTRONIC CO., LTD.

UNLESS OTHERWISE SPECIFIED,TOLERANCE:	DESIGN	DATE	2020.10.18	TITLE:
X.	APPROVED	DATE		1.5间距公座-IP-90度-T0.4
X.x				
X.xx	PART NO		REV: 01	SCALE: 1:1
X.xxx	DRAWING NO	DS-A-4P-R4	SIZE: A4	UNIT: MM
ANGULAR			SHEET: 1/1	