



REV.	DESCRIPTION	DRAW.	DATE.

NOTE:

1. MATERIAL:
 - 1.1 HOUSING: PA9T, UL 94V-0
 - 1.2 TERMINAL: C2680
2. FINISH:
 - 2.1 TERMINAL: NICKEL 50 μ MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Sn ON THE SOLDERING AREA.
3. PRODUCT SPECIFICATION
 - 3.1 CURRENT RATING :5A
 - 3.2 VOLTAGE RATING : 30V AC
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - 3.4 INSULATION RESISTANCE: 100M Ω min.
 - 3.5 CONTACT RESISTANCE: 30m Ω Max.
 - 3.6 Operating Temperature: -40' ~105'

RECOMMENDED PCB LAYOUT
T=1.2MM,TOLERANCES \pm 0.05MM

DISONG ELECTRONIC CO., LTD.

UNLESS OTHERWISE SPECIFIED, TOLERANCE:	DESIGN	DATE	2020.10.18	TITLE:
X	APPROVED	DATE		1.5 间距插座-IP180 度-T0.4
X.x	PART NO	REV: 01		SCALE: 1:1 UNIT: MM
X.xx	DRAWING NO	DS-A-4P-R1	SIZE: A4	SHEET: 1/1
ANGULAR				