



REV.	DESCRIPTION	DRAW.	DATE.

- NOTE:
1. MATERIAL:
 - 1.1 HOUSING: PA9T, UL 94V-0
 - 1.2 TERMINAL: C2680
 2. FINISH:
 - 2.1 TERMINAL: NICKEL 50 μM UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Sn ON THE SOLDERING AREA.
 3. PRODUCT SPECIFICATION
 - 3.1 CURRENT RATING :5A
 - 3.2 VOLTAGE RATING : 30V AC
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - 3.4 INSULATION RESISTANCE: 100MΩ min.
 - 3.5 CONTACT RESISTANCE: 30mΩ Max.
 - 3.6 Operating Temperature: -40° ~105°

RECOMMENDED PCB LAYOUT
 T=1.2MM,TOLERANCES±0.05MM

DISONG ELECTRONIC CO., LTD			
UNLESS OTHERWISE SPECIFIED,TOLERANCE:	DESIGN	W. J. H	DATE 2017.09.28
X.	APPROVED		DATE
X.x	PART NO		REV: 01
X.xx	DRAWING NO		SCALE: 1:1
ANGULAR			UNIT: MM
			SIZE: A4
			SHEET: 1/1