








RECOMMENDED PCB LAYOUT
TOP VIEW(. XX±0.05)

性能:

额定电流: 2.0A

额定电压: 12V

耐电压: 500V

接触电阻: 30mΩ MAX

绝缘电阻: 500MΩ

工作温度: -40℃~+85℃

使用寿命: 5000次以上

塑件(材质): LCP BLACK

接触点(材质): 黄铜C2680,

接触面镀金3U, 焊脚镀金1U

2	HOUSING	PA9T	1	BLACK
1	CONTACT TERMINAL	BRASS	3	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING

DISONG ELECTRONIC CO., LTD.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR				DRAWING	G.B.Wu	DWG.No.	DS-BC-101
PART NO.		BC-0-202A				CHECK	Q.L.Dai	REV.	A0
	UNIT : mm	TOLERANCE OTHERWISE	UP TO 5 ABOVE 5 30 ~ ABOVE 30 ANGLE	±0.2 ±0.3 ±0.5 ±.3°	ANGLE	APPROVAL		DATE	28-08-2017
				0°±3°	SCALE	2:1	PAGE	1 OF 1	