



性能:

额定电流: 3.0A

额定电压: 24V

耐电压: 500V

接触电阻: 30mΩ MAX

绝缘电阻: 500MΩ

工作温度: -40℃~+85℃

塑件(材质): LCP, 耐高温260℃

接触点(材质): 铜合金, 触点镀金3U

RECOMMENDED PCB LAYOUT  
TOP VIEW (.XX±0.05)

PART NO.	DIM A	DIM B
BC-2-240A	8.0	3.0
BC-2-372A	11.0	6.0
BC-2-412A	14.0	9.0
BC-2-505A	17.0	12.0
BC-2-605A	20.0	15.0

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHORUS COPPER	3	Au PLATED

DISONG ELECTRONIC CO., LTD.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME	CONNECTOR		DRAWING	G.B.Wu	DWG.No.	DS-BC-230	
PART NO.	BC-2-240A 372A 412A 505A 605A		CHECK	Q.L.Dai	REV.	A0	
UNIT	mm	TOLERANCE	UP TO 5 ABOVE 5 30 ~ ABOVE 30 ANGLE	±0.2 ±0.3 ±0.5 ±3'	APPROVAL	DATE	15-08-2021
SCALE	2:1	PAGE	1 OF 1				