



RoHS
Compliant








3D VIEW

SYMBOL	REVISION	APPROVAL	DATE

SPECIFICATIONS

- ELECTRICAL CHARACTERISTICS:
 - RATING: DC 12V 3A
 - CONTACT RESISTANCE: 30mΩ MAX (INITIAL)
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
 - INSULATION RESISTANCE: 500MΩ MIN, MEASURED BY 500V DC
- LIFE TEST: MECHANICAL LIFE TEST 5,000 CYCLES.
- TEMPERATURE RISE : 30° C MAX



产品型号	DIM: A	DIM: B
BC-1-104	3.00	1.80
BC-1-221	6.00	3.00
BC-1-341	9.00	6.00
BC-1-432	12.00	9.00
BC-1-516	15.00	12.00
BC-1-618	18.00	15.00
BC-1-708	21.00	18.00
BC-1-807	24.00	21.00
BC-1-903	27.00	24.00
BC-1-1003	30.00	27.00

2	HOUSING	LCP	1	GRAY
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED
	NO. PARTS	MATERIAL	QTY.	FINISHING

东莞市迪松电子科技有限公司

GUANGDONG NUODE ELECTRONIC TECHNOLOGY CO., LTD

PART NAME	CONNECTOR	DRAWING	B. J. Zheng	DWG. No.	
PART NO.	92-1-104 221 341 432 516 618 708 807 903 1003	CHECK	X. M. Chen	REV.	A1
UNIT:	TOLERANCE	ANGLE	APPROVAL	DATE	10-10-2023
mm	OTHERWISE: ± 0.10 ± 0.15 ± 0.20 ± 0.30 ± 0.40 ± 0.50 ± 0.60 ± 0.80 ± 1.00	SCALE	3:1	PAGE	1 OF 1