



RECOMMENDED PCB LAYOUT
TOP VIEW (.XX±0.05)

性能：
 额定电流：3.0A
 额定电压：12V
 耐电压：500V
 接触电阻：30mΩ MAX
 绝缘电阻：500MΩ
 工作温度：-40℃~+85℃
 塑件（材质）：LCP黑色
 接触点（材质）：铜合金，触点镀金3U”

PART NO.	DIM A	DIM B	DIM C	NO.	PARTS	MATERIAL	QTY.	FINISHING
BC-2-301	8.0	5.70±0.3	6.85±0.3	2	HOUSING	LCP	1	BLACK
BC-2-301A	9.25	6.95±0.3	8.10±0.3	1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED
BC-2-301B	10.50	8.20±0.3	9.35±0.3	NO.	PARTS	MATERIAL	QTY.	FINISHING

DISONG ELECTRONIC CO., LTD.		PART NAME		CONNECTOR		DRAWING		G.B.Wu		DWG.No.		DS-BC-85	
		PART NO.		BC-2-301 301A 301B		CHECK		Q.L.Dai		REV.		A0	
COPYRIGHT RESERVED, PLEASE DO NOT COPY.		UNIT : mm		TOLERANCE : OTHERWISE		ANGLE : UP TO 5° ±0.2, ABOVE 5 30° ~ ±0.3, ABOVE 30° ±0.5, ±3°		APPROVAL		DATE		03-09-2012	
						SCALE : 2:1		PAGE		1 OF 1			